

WHAT IS CLAIMED IS:

1. A cleaning method for cleaning a developer container, comprising:

5 a step of blowing air through an opening formed in said developer container at a first flow rate;

a step of sucking air through the opening at a second flow rate which is larger than the first flow rate;

10 wherein while said blowing and suction steps are being simultaneously carried out, ambient air is permitted to enter said developer container through an ambient air inlet.

15 2. A method according to Claim 1, wherein said ambient air inlet is disposed at the position opposite from said opening with respect to a longitudinal direction of said developer container.

20 3. A method according to Claim 1, further comprising a step of inserting an air nozzle into said developer container.

25 4. A method according to Claim 3, wherein the air is blown through a plurality of air blowing ports in directions perpendicular to a longitudinal direction of said air nozzle at different positions

10040763.010902

with respect to a circumferential direction of said air nozzle.

5 5. A method according to Claim 3, wherein in
said inserting step, and one first and second air
nozzles are inserted, and the air is blown through a
plurality of air blowing ports of the first air nozzle
in directions perpendicular to a longitudinal
direction of said air nozzle at different positions
10 with respect to a circumferential direction of said
air nozzle, and the air is blown through an air
blowing port provided at a longitudinal end of the
second air nozzle in a longitudinal direction of the
second air nozzle.

15 6. A method according to Claim 5, wherein a
blowing rate of the first air nozzle is larger than a
blowing rate of the second air nozzle.

20 7. A method according to Claim 1, wherein said
blowing step and suction step are carried out
simultaneously while said developer container is
rotated.

25 8. A method according to Claim 1, wherein said
blowing step and said suction step are carried out
simultaneously while reciprocating said developer

206010"ESZ04001

container in a longitudinal direction thereof.

9. A method according to Claim 1, wherein said
blowing step is carried out after start of said
5 suction step.

10. A recycling method for recycling a developer
container, comprising:

10 a step of removing first and second sealing
members sealing first and second opening openings
provided in said developer container;

a step of blowing air through an opening
formed in said developer container at a first flow
rate;

15 a step of sucking air through the opening at
a second flow rate which is larger than the first flow
rate;

a step of filling a developer into said
developer container;

20 instead of mounting said first and second
sealing members to seal said first and second
openings;

wherein wherein while said blowing and
suction steps are being simultaneously carried out,
25 ambient air is permitted to enter said developer
container through an ambient air inlet.

10040753-010902

11. A method according to Claim 10, wher in said ambient air inlet is said second opening disposed at a position opposite from said first opening with respect to a longitudinal direction of said developer container.

12. A method according to Claim 10. further comprising a step of inserting an air nozzle into said developer container.

13. A method according to Claim 12, wherein the air is blown through a plurality of air blowing ports in directions perpendicular to a longitudinal direction of said air nozzle at different positions with respect to a circumferential direction of said air nozzle.

14. A method according to Claim 12, wherein in said inserting step, and one first and second air nozzles are inserted, and the air is blown through a plurality of air blowing ports of the first air nozzle in directions perpendicular to a longitudinal direction of said air nozzle at different positions with respect to a circumferential direction of said air nozzle, and the air is blown through an air blowing port provided at a longitudinal end of the second air nozzle in a longitudinal direction of the

2067093 "010902

second air nozzle.

15. A method according to Claim 14, wherein a
blowing rate of the first air nozzle is larger than a
5 blowing rate of the second air nozzle.

16. A method according to Claim 10, wherein said
blowing step and suction step are carried out
simultaneously while said developer container is
10 rotated.

17. A method according to Claim 10, wherein said
blowing step and said suction step are carried out
simultaneously while reciprocating said developer
15 container in a longitudinal direction thereof.

18. A method according to Claim 10, wherein said
blowing step is carried out after start of said
suction step.

20

25

20040763-010902